

- 4) Leaf is not recessed and closes flush with the perimeter frame
- 5) All exposed hardware; operator, lock & hinges are dry-powder painted the same color with window.
- 6) Left-right, Top-bottom configurations achieved by common heads, common sills and common jambs.

- 7) Special Hinges and attachments make it the only metal casement on the market where the hinges are not fastened by drilling into the perimeter frame.



- Attractive looks
- Different units are consolidated into one unit creating very clean lines
- Same color hinges disappear into the frame
- Raising or lowering of the leaf can be done by anybody in the field.



SCREENS

- 8) Interior extruded screen is recessed and without any exposed clips/screws.
- 9) Proprietary concealed ball catch hardware

- Easy screen removal and mount reinstallation for washing the glass

<u>Security</u>		
<p>1) Progressive Multi-Point Locking</p> <p>2) Leaf opens 95 degrees</p> <p>3) Stainless Steel limiting device is standard</p>	<ul style="list-style-type: none"> • Safety • Allows leaf to be flush with the perimeter frame <i>Example: 26 inch window width achieves egress in some tight situations.</i> • Allows the casement to be opened on windy days. 	
<u>Performance</u>		
<p>1) Double weather seals</p> <p>2) Very durable extruded Screen</p> <p>3) Folding Handle</p> <p>4) Double sealed insulated glass with steel spacers</p>	<ul style="list-style-type: none"> • High degree of stopping water, air, dust and bug penetration • Same color as window • Allows more flexible interior window treatment options • Provides an extra barrier against heat transfer. Similar benefits to a "warm edge spacer" • Non-pro rated 10 year seal warranty 	

<p>5) Thermal Break</p>	<ul style="list-style-type: none">• C-30 rating on 36"x78" tested unit• U value = 0.48 and SHGC = .20 (with LoE-366 glass and argon gas)• Double Color available for the frames	